



Heater coil carries a 5-year warranty

North America's #1 Manufacturer of High-Quality Cleaning Equipment

Safety pressure-relief valve protects machine and user from

Float tank, with rugged brass input fitting and float valve, helps maintain constant pressure and flow

and traps sediment or debris.

It is recessed at center

Circuit Interrupter

against shock hazard

Hotsy-designed

a 7-Year warranty

triplex pumps carry

(GFCI breaker) provides additional protection

and balance

Ground Fault

of chassis for protection

heat expansion

and 790SS Hot Water **Pressure Washers**

Electric / Belt Drive

Upright, oil fired burner delivers high efficiency with diesel fuel, kerosene or home-heating oil

> **Control panel** includes adjustable temperature control plus heavy-duty heater and pump motor

> > 5 HP. 230V. 1 PH Baldor electric motor (Model 795SS) comes with thermal overload protection and manual reset

Rugged belt drive provides smooth, quiet operation and outstanding reliability

Rust-proof polyethylene fuel tank includes easy-access drain and fuel gauge in cap

Model **795SS**

3.5 GPM @2000 PSI

Convenient hose-reel bracket accepts swivel or stationary reels

Belt tension adjusts easily

by turning a single bolt

Variable upstream detergent injection ensures high-pressure

sudsing

FEATURES

- 2.8 or 3.5 GPM @ 2000 PSI
- Oil Fired Burners
- 208V or 230V, 1PH
- 1330 or 1490 RPM Belt Drive Pumps

Pneumatic tires with inner tubes provide easy maneuverability over pavement or rough terrain



Built-in wand and nozzle holders provide convenient storage

Oil Fired Burners

■ 2.8 or 3.5 GPM @ 2000 PSI

■ Hotsy 7-Year Pump Warranty

■ 1330 or 1490 RPM Belt Drive Pumps

Designed for tough, industrial cleaning.

SPECIFICATIONS													BELT DRIVE	
MODEL	GPM	PSI	НР	MOTOR RPM	VOLT/PH	AMP	FUEL	PUMP	PUMP RPM	DRIVE	PORTABILITY	HOSE	SHIP WT (lbs)	
790SS	2.8	2000	4TEFC*	1725	230/1	20	Oil	Hotsy Triplex	1330	Belt	Std	50'	460	
790SS-208	2.8	2000	4TEFC*	1725	208/1	22	Oil	Hotsy Triplex	1330	Belt	Std	50'	460	
795SS	3.5	2000	5	3450	230/1	24	Oil	Hotsy Triplex	1490	Belt	Std	50'	500	
795SS-208	3.5	2000	5	3450	208/1	27	Oil	Hotsy Triplex	1490	Belt	Std	50'	500	

^{*}Totally enclosed fan cooled (TEFC)



Clean better with **Hotsy detergents**

Hotsy pressure washers clean best when matched with our specially-formulated Hotsy detergents. Nearly all 40 Hotsy detergent formulations contain Hotsy's exclusive advanced-formula HCC additives to help prevent scale build-up and fight corrosion in your equipment. Most Hotsy detergents are USDA and Canadian Agriculture approved. All are highly concentrated, so a little goes a long way.


Spend some time with a Hotsy Expert

Hotsy has more than 130 local Sales & Service Distributors in North America, all factorytrained to properly evaluate your highpressure cleaning needs.

Rely on our network of seasoned service professionals for the safest, most effective and most efficient solution to your specific cleaning need.







Hotsy's upright burner design provides maximum efficiency for fast heating, easy venting in indoor applications, plus excellent fuel economy.

OPTIONS-795SS and 790SS

■ 8" Oil-Fired Draft Dampener barometric; prevents backdrafts and keeps cold air out.

Hotsy Accessories customize your application for top performance



non-pivot hose reels keep hose neatly stored and shop areas safe



to 24' to reach high places without scaffolding High-pressure






Rotary surface cleaner attaches

to your pressure washer; reduces

overspray and zebra striping

Telescoping wands extend



Foamers increase dwell time on vertical surfaces, such as tractor trailers, walls and crates



Tel: (800) 525-1976 Fax: (888) 880-9631

www.Hotsy.com email: info@Hotsy.com P/N 97-0444 Effective 9/05 Specification to change without notice. ©2005 Hotsy Specifications & product descriptions subject to change without notice.

NOTE: We are constantly improving and updating our products. Consequently, pictures, features & specifications in this brochure may differ slightly from current models. Flow rates & pressure ratings may vary due to variances allowed by manufacturers of our machine components. We attempt to keep our machine performance within ±5% of listed specifications.